

29 118 EN0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH ONE VALVE



PRODUKTO APRAŠYMAS

- Spalva: brushed nickel
- set for final installation for
- GROHE Rapido SmartBox 35 600/35 604
- metal wall escutcheon with GROHE FastFixation (covered escutcheon and shaft sealing, covered fixing), retroactively 6° adjustable
- GROHE Long-Life finish
- GROHE SmartControl push for ON-OFF, turn for volume adjustment from GROHE Water Saving to full flow
- exchangeable symbols
- GROHE TurboStat compact cartridge with wax thermoelement
- GROHE SafeStop at 38°C
- GROHE SafeStop Plus optional temperature limiter at 43°C or 46°C included
- built-in non return valves and dirt strainers
- without roughing-in-set
- flow performance: outlet A (to external shut-off) = 34 l/min outlet B/C = 29 l/min

29 118 EN0 GROHTHERM SMARTCONTROL THERMOSTAT FOR CONCEALED INSTALLATION WITH ONE VALVE



ATSARGINĖS DALYS , sausio 2020 – dabar

- 1: Mounting plate (Produkto nr. 48362000)
- 2: Temperature control handle (Produkto nr. 49029EN0)
- 3: Escutcheon (Produkto nr. 49030EN0)
- 4: Push button (Produkto nr. 48361BE0)
- 5: Cartridge (Produkto nr. 48359000)
- 5.1: Spindle (Produkto nr. 49088000)
- 6: Thermostatic compact cartridge 3/4" (Produkto nr. 49028000)
- 7: Non-return valve (Produkto nr. 47753000)
- 8: Seal (Produkto nr. 48360000)
- 9: Socket spanner (Produkto nr. 49059000)*
- 10: GROHE TurboStat cartridge 3/4" (Produkto nr. 49003000)*
- 11: Service stops (Produkto nr. 1405300M)*
- 12: Universal extension set single-lever mixers, 25 mm (Produkto nr. 14048000)*

* pasirenkami priedai